

ALL-WEATHER

ClimaFlex 4S

The ultimate all-weather CUV/SUV and touring tire engineered for durability and performance.



KEY ATTRIBUTES

70K

700
AA



M+S

POPULAR FITMENTS

- Nissan Versa
- Honda CRV
- Kia Forte
- Toyota Corolla
- Ford Escape

ALL-WEATHER RATED



RAIN



MIX



SNOW



HEAT

FEATURES & BENEFITS

1. Increased Snow Traction

Central groove enhancers offer increased winter capabilities

2. Enhanced Aesthetics

Innovative “Fortune Four” pattern improves tread style without sacrificing performance

3. Superb Handling

Advanced 3D siping enhances tread rigidity, improving cornering and braking, while full-depth sipes provide exceptional wet braking

4. Extended Lifespan

Symmetric pattern ensures easy tire rotation, extending lifespan and saving on replacements

5. All-Weather Optimized

3PMS-rated for superior performance in wet and wintry conditions



**FORTUNE
TIRES** 

EXPECT MORE™

Available in 61
3PMS-rated SKUs.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com





TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
185/65R15	XL	92H	700 A A	17	5.5	5.0 - 6.5	50	1389	24.4	7.4	10	1N+2S+1P
195/65R15	SL	91H	700 A A	16	6.0	5.5 - 7.0	51	1356	25.0	7.9	10	1N+2S+1P
205/55R16	XL	94H	700 A A	21	6.5	5.5 - 7.5	51	1356	24.9	8.4	10	1N+2S+1P
205/60R16	XL	96V	700 A A	25	6.0	5.5 - 7.5	50	1565	25.7	8.2	10	1N+2S+2P
205/65R16	XL	99H	700 A A	27	6.0	5.5 - 7.5	50	1709	26.5	8.2	10	1N+2S+2P
215/55R16	XL	97H	700 A A	22	7.0	6.0 - 7.5	50	1609	25.3	8.9	10	1N+2S+2P
215/60R16	SL	95H	700 A A	23	6.5	6.0 - 7.5	51	1521	26.1	8.7	10	1N+2S+2P
215/65R16	XL	102H	700 A A	27	6.5	6.0 - 7.5	50	1874	27.0	8.7	10	1N+2S+2P
215/70R16	SL	100H	700 A A	27	6.5	5.5 - 7.0	51	1764	27.9	8.7	10	1N+2S+2P
225/60R16	SL	98H	700 A A	28	6.5	6.0 - 8.0	51	1653	26.6	9.0	10	1N+2S+2P
235/70R16	SL	106H	700 A A	27	7.0	6.0 - 8.0	51	2094	29.0	9.4	10	1N+2S+2P
205/50R17	XL	93V	700 A A	27	6.5	5.5 - 7.5	50	1433	25.1	8.4	10	1N+2S+1P
205/55R17	XL	95H	700 A A	27	6.5	5.5 - 7.5	50	1521	25.9	8.4	10	1N+2S+2P
215/45R17	XL	91V	700 A A	20	7.0	7.0 - 8.0	50	1356	24.6	8.4	10	1N+2S+1P
215/50R17	XL	95V	700 A A	28	7.0	6.0 - 7.5	50	1521	25.5	8.9	10	1N+2S+2P
215/55R17	XL	98V	700 A A	25	7.0	6.0 - 7.5	50	1653	26.3	8.9	10	1N+2S+2P
215/60R17	SL	96H	700 A A	27	6.5	6.0 - 7.5	51	1565	27.2	8.7	10	1N+2S+2P
215/65R17	SL	99H	700 A A	27	6.5	6.0 - 7.5	51	1709	28.0	8.7	10	1N+2S+2P
225/45R17	XL	94V	700 A A	28	7.5	7.0 - 8.5	50	1477	25.0	8.9	10	1N+2S+1P
225/50R17	XL	98V	700 A A	25	7.0	6.0 - 8.0	50	1653	25.9	9.2	10	1N+2S+2P
225/55R17	SL	97V	700 A A	26	7.0	6.0 - 8.0	51	1609	26.8	9.2	10	1N+2S+2P
225/60R17	SL	99H	700 A A	27	6.5	6.0 - 8.0	51	1709	27.6	9.0	10	1N+2S+2P
225/65R17	SL	102H	700 A A	27	6.5	6.0 - 8.0	51	1874	28.5	9.0	10	1N+2S+2P
235/50R17	SL	96V	700 A A	28	7.5	6.5 - 8.5	51	1565	26.3	9.6	10	1N+2S+2P
235/55R17	XL	103V	700 A A	27	7.5	6.5 - 8.5	50	1929	27.2	9.6	10	1N+2S+2P
235/60R17	SL	102H	700 A A	27	7.0	6.5 - 8.5	51	1874	28.1	9.4	10	1N+2S+2P
235/65R17	XL	108V	700 A A	30	7.0	6.5 - 8.5	50	2205	29.1	9.4	10	1N+2S+2P
245/65R17	XL	111H	700 A A	28	7.0	7.0 - 8.5	50	2403	29.5	9.8	10	1N+2S+2P
215/55R18	XL	99V	700 A A	28	7.0	6.0 - 7.5	50	1709	27.3	8.9	10	1N+2S+2P
225/40R18	XL	92V	700 A A	27	8.0	7.5 - 9.0	50	1389	25.1	9.1	10	1N+2S+1P
225/45R18	XL	95V	700 A A	27	7.5	7.0 - 8.5	50	1521	25.9	8.9	10	1N+2S+2P
225/50R18	XL	99V	700 A A	28	7.0	6.0 - 8.0	50	1709	26.9	9.2	10	1N+2S+2P
225/55R18	SL	98V	700 A A	26	7.0	6.0 - 8.0	51	1653	27.8	9.2	10	1N+2S+2P
225/60R18	XL	104H	700 A A	27	6.5	6.0 - 8.0	50	1984	28.6	9.0	10	1N+2S+2P
235/45R18	XL	98V	700 A A	25	8.0	7.5 - 9.0	50	1653	26.3	9.3	10	1N+2S+2P
235/50R18	XL	101V	700 A A	27	7.5	6.5 - 8.5	50	1819	27.3	9.6	10	1N+2S+2P
235/55R18	XL	104V	700 A A	28	7.5	6.5 - 8.5	50	1984	28.1	9.6	10	1N+2S+2P
235/60R18	XL	107V	700 A A	29	7.0	6.5 - 8.5	50	2149	29.1	9.4	10	1N+2S+2P
235/65R18	XL	110H	700 A A	28	7.0	6.5 - 8.5	50	2337	30.0	9.4	10	1N+2S+2P
245/40R18	XL	97V	700 A A	29	8.5	8.0 - 9.5	50	1609	25.7	9.8	10	1N+2S+2P
245/45R18	XL	100V	700 A A	28	8.0	7.5 - 9.0	50	1764	26.7	9.6	10	1N+2S+2P
245/60R18	SL	105V	700 A A	31	7.0	7.0 - 8.5	51	2039	29.6	9.8	10	1N+2S+2P
255/60R18	SL	108H	700 A A	29	7.5	7.0 - 9.0	51	2205	30.0	10.2	10	1N+2S+2P
255/65R18	SL	111H	700 A A	29	7.5	7.0 - 9.0	51	2403	31.1	10.2	10	1N+2S+2P
265/60R18	SL	110H	700 A A	29	8.0	7.5 - 9.5	51	2337	30.5	10.7	10	1N+2S+2P
225/55R19	XL	103V	700 A A	28	7.0	6.0 - 8.0	50	1929	28.8	9.2	10	1N+2S+2P
235/40R19	XL	96V	700 A A	26	8.5	8.0 - 9.5	50	1565	26.4	9.5	10	1N+2S+2P
235/45R19	SL	95V	700 A A	28	8.0	7.5 - 9.0	51	1521	27.4	9.3	10	1N+2S+2P
235/50R19	XL	103V	700 A A	27	7.5	6.5 - 8.5	50	1929	28.3	9.6	10	1N+2S+2P
235/55R19	XL	105V	700 A A	30	7.5	6.5 - 8.5	50	2039	29.2	9.6	10	1N+2S+2P
245/45R19	XL	102V	700 A A	29	8.0	7.5 - 9.0	50	1874	27.7	9.6	10	1N+2S+2P
245/55R19	XL	107V	700 A A	29	7.5	7.0 - 8.5	50	2149	29.6	10.0	10	1N+2S+2P
255/60R19	XL	113V	700 A A	28	7.5	7.0 - 9.0	50	2535	31.1	10.2	10	1N+2S+2P
235/55R20	SL	102V	700 A A	31	7.5	6.5 - 8.5	51	1874	30.2	9.6	10	1N+2S+2P
245/50R20	XL	105V	700 A A	32	7.5	7.0 - 8.5	50	2039	29.7	10.0	10	1N+2S+2P
255/45R20	XL	105V	700 A A	29	8.5	8.0 - 9.5	50	2039	29.1	10.0	10	1N+2S+2P
255/50R20	XL	109V	700 A A	29	8.0	7.0 - 9.0	50	2271	30.1	10.4	10	1N+2S+2P
255/55R20	XL	110V	700 A A	36	8.0	7.0 - 9.0	50	2337	31.0	10.4	10	1N+2S+2P
265/50R20	SL	107V	700 A A	29	8.5	7.5 - 9.5	51	2149	30.5	10.9	10	1N+2S+2P
275/55R20	XL	117H	700 A A	30	8.5	7.5 - 9.5	50	2833	31.9	11.2	10	1N+2S+2P
285/45R22	XL	114H	700 A A	19	9.5	9.0 - 10.5	50	2601	32.1	11.2	10	1N+2S+2P


TOURING

Perfectus

A premium all-season touring tire with an asymmetrical tread design, providing superior handling and performance.



KEY ATTRIBUTES



POPULAR FITMENTS

- Nissan Versa
- Honda CRV
- Kia Forte
- Toyota Corolla
- Ford Escape

FEATURES & BENEFITS

1. Superb Handling

Asymmetrical tread design boosts performance when passing and cornering

2. Increased Wet Traction

Four wide grooves improve handling in wet conditions

3. Wet Braking Optimized

Unique siping and pattern design enhances traction and braking in wet conditions

4. Extended Lifespan

Continuous rib design provides stability and reduces abnormal wear

5. Road Noise Resistant

Pattern Noise Simulation (PNS) produces a quieter ride

6. Clearly Labeled Sidewalls

Marked "inside" and "outside" for ease of installation



**FORTUNE
TIRES** 

EXPECT MORE™

Fortune's highest
volume seller.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com





TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
175/65R14	SL	82T	540 A A	15	5.0	5.0 - 6.0	44	1047	23.0	7.0	9	1N+2S+1P
175/70R14	SL	84T	540 A A	16	5.0	4.5 - 6.0	44	1102	23.7	7.0	9	1N+2S+1P
185/65R14	SL	86H	540 A A	16	5.5	5.0 - 6.5	44	1168	23.5	7.4	9	1N+2S+1P
195/70R14	SL	91T	600 A A	19	6.0	5.0 - 6.5	44	1356	24.8	7.9	9	1N+2S+2P
165/50R15	SL	72V	540 A A	13	5.0	5.0 - 6.0	44	783	21.5	6.7	9	1N+2S+1P
175/55R15	SL	77H	540 A A	16	5.5	5.0 - 6.0	44	908	22.6	7.2	9	1N+2S+1P
175/65R15	SL	84H	540 A A	16	5.0	5.0 - 6.0	44	1102	24.0	7.0	9	1N+2S+1P
185/55R15	SL	82V	540 A A	16	6.0	5.0 - 6.5	44	1047	23.0	7.6	10	1N+2S+1P
185/60R15	SL	84H	520 A A	16	5.5	5.0 - 6.5	44	1102	23.7	7.4	9	1N+2S+1P
185/65R15	SL	88H	540 A A	17	5.5	5.0 - 6.5	44	1235	24.4	7.4	9	1N+2S+1P
195/50R15	XL	86V	600 A A	17	6.0	5.5 - 7.0	50	1168	22.7	7.9	10	1N+2S+1P
195/55R15	SL	85V	600 A A	17	6.0	5.5 - 7.0	44	1135	23.4	7.9	10	1N+2S+1P
195/60R15	SL	88H	600 A A	11	6.0	5.5 - 7.0	44	1235	24.2	7.9	10	1N+2S+1P
195/65R15	SL	91H	600 A A	19	6.0	5.5 - 7.0	44	1356	25.0	7.9	10	1N+2S+1P
205/65R15	XL	99H	600 A A	21	6.0	5.5 - 7.5	50	1709	25.5	8.2	10	1N+2S+2P
205/70R15	SL	96H	600 A A	22	6.0	5.0 - 7.0	44	1565	26.3	8.2	10	1N+2S+2P
215/70R15	SL	98T	600 A A	24	6.5	5.5 - 7.0	44	1653	26.9	8.7	10	1N+2S+2P
185/55R16	SL	83H	540 A A	17	6.0	5.0 - 6.5	44	1074	24.0	7.6	10	1N+2S+1P
195/50R16	SL	84V	600 A A	18	6.0	5.5 - 7.0	44	1102	23.7	7.9	10	1N+2S+1P
195/55R16	SL	87V	600 A A	18	6.0	5.5 - 7.0	44	1201	24.4	7.9	10	1N+2S+1P
205/55R16	XL	94V	600 A A	21	6.5	5.5 - 7.5	50	1477	24.9	8.4	10	1N+2S+1P
205/60R16	SL	92V	600 A A	21	6.0	5.5 - 7.5	44	1389	25.7	8.2	10	1N+2S+1P
205/65R16	SL	95H	600 A A	22	6.0	5.5 - 7.5	44	1521	26.5	8.2	10	1N+2S+2P
205/70R16	SL	97H	600 A A	24	6.0	5.0 - 7.0	44	1609	27.3	8.2	10	1N+2S+2P
215/55R16	XL	97V	600 A A	22	7.0	6.0 - 7.5	50	1609	25.3	8.9	10	1N+2S+2P
215/60R16	SL	95V	600 A A	23	6.5	6.0 - 7.5	44	1521	26.1	8.7	10	1N+2S+2P
215/65R16	SL	98H	600 A A	24	6.5	6.0 - 7.5	44	1653	27.0	8.7	10	1N+2S+2P
215/70R16	SL	100H	600 A A	26	6.5	5.5 - 7.0	44	1764	27.9	8.7	10	1N+2S+2P
225/60R16	SL	98V	600 A A	25	6.5	6.0 - 8.0	44	1653	26.6	9.0	10	1N+2S+2P
225/65R16	SL	100H	600 A A	25	6.5	6.0 - 8.0	44	1764	27.5	9.0	10	1N+2S+2P
225/70R16	SL	103H	600 A A	27	6.5	6.0 - 7.5	44	1929	28.4	9.0	10	1N+2S+2P
235/60R16	SL	100H	600 A A	26	7.0	6.5 - 8.5	44	1764	27.1	9.4	10	1N+2S+2P
235/65R16	SL	103H	600 A A	27	7.0	6.5 - 8.5	44	1929	28.0	9.4	10	1N+2S+2P
235/70R16	SL	106H	600 A A	29	7.0	6.0 - 8.0	44	2094	29.0	9.4	10	1N+2S+2P
205/50R17	XL	93V	600 A A	20	6.5	5.5 - 7.5	50	1433	25.1	8.4	10	1N+2S+1P
215/50R17	XL	95V	600 A A	22	7.0	6.0 - 7.5	50	1521	25.5	8.9	10	1N+2S+2P
215/55R17	SL	94V	600 A A	24	7.0	6.0 - 7.5	44	1477	26.3	8.9	10	1N+2S+1P
215/60R17	XL	100H	600 A A	24	6.5	6.0 - 7.5	50	1764	27.2	8.7	10	1N+2S+2P
215/65R17	SL	99H	600 A A	25	6.5	6.0 - 7.5	44	1709	28.0	8.7	10	1N+2S+2P
225/50R17	XL	98V	600 A A	24	7.0	6.0 - 8.0	50	1653	25.9	9.2	10	1N+2S+2P
225/55R17	SL	97V	600 A A	25	7.0	6.0 - 8.0	44	1609	26.8	9.2	10	1N+2S+2P
225/60R17	SL	99V	600 A A	25	6.5	6.0 - 8.0	44	1709	27.6	9.0	10	1N+2S+2P
225/65R17	SL	102H	600 A A	27	6.5	6.0 - 8.0	44	1874	28.5	9.0	10	1N+2S+2P
235/50R17	SL	96V	600 A A	25	7.5	6.5 - 8.5	44	1565	26.3	9.6	10	1N+2S+2P
235/55R17	SL	99V	600 A A	26	7.5	6.5 - 8.5	44	1709	27.2	9.6	10	1N+2S+2P
235/60R17	SL	102V	600 A A	27	7.0	6.5 - 8.5	44	1874	28.1	9.4	10	1N+2S+2P
235/65R17	XL	108V	600 A A	29	7.0	6.5 - 8.5	50	2205	29.1	9.4	10	1N+2S+2P
245/50R17	SL	99V	600 A A	26	7.5	7.0 - 8.5	44	1709	26.7	10.0	10	1N+2S+2P
215/55R18	SL	95V	600 A A	24	7.0	6.0 - 7.5	44	1521	27.3	8.9	10	1N+2S+2P
225/55R18	SL	98V	600 A A	26	7.0	6.0 - 8.0	44	1653	27.8	9.2	10	1N+2S+2P
225/60R18	SL	100V	600 A A	28	6.5	6.0 - 8.0	44	1764	28.6	9.0	10	1N+2S+2P
235/50R18	SL	97V	600 A A	26	7.5	6.5 - 8.5	44	1609	27.3	9.6	10	1N+2S+2P
235/55R18	SL	100V	600 A A	27	7.5	6.5 - 8.5	44	1764	28.1	9.6	10	1N+2S+2P
235/60R18	SL	103V	600 A A	28	7.0	6.5 - 8.5	44	1929	29.1	9.4	10	1N+2S+2P
235/65R18	SL	106H	600 A A	29	7.0	6.5 - 8.5	44	2094	30.0	9.4	10	1N+2S+2P
245/55R18	SL	103V	600 A A	29	7.5	7.0 - 8.5	44	1930	28.6	10.0	10	1N+2S+2P
245/60R18	SL	105V	600 A A	30	7.0	7.0 - 8.5	44	2039	29.6	9.8	10	1N+2S+2P
255/65R18	SL	111H	600 A A	33	7.5	7.0 - 9.0	44	2403	31.1	10.2	10	1N+2S+2P
235/40R19	XL	96V	600 A A	25	8.5	7.0 - 9.5	50	1565	31.1	10.2	10	1N+2S+2P

All specifications subject to change

ULTRA HIGH-PERFORMANCE

Viento

A high-speed rated,
precision engineered,
all-season tire for
high-performance vehicles.



KEY ATTRIBUTES

50K

500
AA

M+S

POPULAR FITMENTS

- Ford Mustang
- Tesla Model 3
- Toyota Camry
- Volkswagen Jetta
- Volvo 560

FEATURES & BENEFITS

1. Hydroplaning Resistant

Unique tread pattern effectively evacuates water, reduces lift, and enhances wet braking

2. High-Speed Rated

Assymetrical tread design improves performance at highway speeds

3. Road Noise Resistant

Pattern Noise Simulation (PNS) produces a quieter ride

4. Increased Durability

Nano Blend Compound ensures consistent performance over the lifecycle of the tire

5. Clearly Labeled Sidewalls

Marked "inside" and "outside" for ease of installation



**FORTUNE
TIRES** 

EXPECT MORE™

An affordable alternative
to premium tier tires.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com



TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
205/45ZR16	XL	87W	500 A A	20	7.0	6.5 - 7.5	50	1201	23.2	8.1	10	1N+2S+1P
205/55ZR16	XL	94W	500 A A	20	6.5	5.5 - 7.5	50	1477	24.9	8.4	10	1N+2S+1P
215/55ZR16	XL	97W	500 A A	22	7.0	6.0 - 7.5	50	1609	25.3	8.9	10	1N+2S+2P
215/55ZR16	XL	97W	500 A A	22	7.0	6.0 - 7.5	50	1609	25.3	8.9	10	1N+2S+2P
205/45ZR17	XL	88W	500 A A	19	7.0	6.5 - 7.5	50	1235	24.3	8.1	10	1N+2S+1P
205/50ZR17	XL	93W	500 A A	21	6.5	5.5 - 7.5	50	1433	25.1	8.4	10	1N+2S+1P
215/45ZR17	XL	91W	500 A A	21	7.0	7.0 - 8.0	50	1356	24.6	8.4	10	1N+2S+1P
215/50ZR17	XL	95W	500 A A	22	7.0	6.0 - 7.5	50	1521	25.5	8.9	10	1N+2S+2P
215/55ZR17	SL	94W	500 A A	24	7.0	6.0 - 7.5	51	1477	26.3	8.9	10	1N+2S+1P
225/45ZR17	XL	94W	500 A A	21	7.5	7.0 - 8.5	50	1477	25.0	8.9	10	1N+2S+1P
225/50ZR17	XL	98W	500 A A	24	7.0	6.0 - 8.0	50	1653	25.9	9.2	10	1N+2S+2P
225/55ZR17	SL	97W	500 A A	25	7.0	6.0 - 8.0	44	1609	26.8	9.2	10	1N+2S+2P
235/45ZR17	XL	97W	500 A A	24	8.0	7.5 - 9.0	50	1609	25.4	9.3	10	1N+2S+2P
235/55ZR17	SL	99W	500 A A	26	7.5	6.5 - 8.5	51	1709	27.2	9.6	10	1N+2S+2P
245/40ZR17	XL	95W	500 A A	24	8.5	8.0 - 9.5	50	1521	24.7	9.8	10	1N+2S+2P
245/45ZR17	XL	99Y	500 A A	25	8.0	7.5 - 9.0	50	1709	25.7	9.6	10	1N+2S+2P
255/40ZR17	XL	98W	500 A A	24	9.0	8.5 - 10.0	50	1653	25.0	10.2	10	1N+2S+1P
275/40ZR17	XL	102W	500 A A	26	9.5	9.0 - 11.0	50	1875	25.7	10.9	10	1N+2S+2P
215/45ZR18	XL	93Y	500 A A	21	7.0	7.0 - 8.0	50	1433	25.6	8.4	10	1N+2S+1P
225/40ZR18	XL	92Y	500 A A	21	8.0	7.5 - 9.0	50	1389	25.1	9.1	10	1N+2S+1P
225/45ZR18	XL	95Y	500 A A	24	7.5	7.0 - 8.5	50	1521	25.9	8.9	10	1N+2S+2P
225/50ZR18	SL	95Y	500 A A	25	7.0	6.0 - 8.0	44	1521	26.9	9.2	10	1N+2S+2P
235/40ZR18	XL	95Y	500 A A	25	8.5	8.0 - 9.5	50	1521	25.4	9.5	10	1N+2S+2P
235/45ZR18	XL	98Y	500 A A	25	8.0	7.5 - 9.0	50	1653	26.3	9.3	10	1N+2S+2P
235/50ZR18	XL	101Y	500 A A	26	7.5	6.5 - 8.5	50	1819	27.3	9.6	10	1N+2S+2P
245/35ZR18	XL	92Y	500 A A	22	8.5	8.0 - 9.5	50	1389	24.8	9.8	10	1N+2S+1P
245/40ZR18	XL	97Y	500 A A	25	8.5	8.0 - 9.5	50	1609	25.7	9.8	10	1N+2S+2P
245/25ZR18	XL	100Y	500 A A	26	8.0	7.5 - 9.0	50	1764	26.7	9.6	10	1N+2S+2P
255/35ZR18	XL	94Y	500 A A	23	9.0	8.5 - 10.0	50	1477	25.0	10.2	9	1N+2S+1P
255/40ZR18	XL	99Y	500 A A	26	9.0	8.5 - 10.0	50	1709	26.0	10.2	10	1N+2S+2P
255/45ZR18	XL	103Y	500 A A	27	8.5	8.0 - 9.5	50	1929	27.0	10.0	10	1N+2S+2P
265/35ZR18	XL	97Y	500 A A	26	9.5	9.0 - 10.5	50	1609	25.3	10.7	9	1N+2S+2P
275/35ZR18	XL	99W	500 A A	26	9.5	9.0 - 11.0	50	1710	25.6	10.9	9	1N+2S+2P
275/40ZR18	XL	103Y	500 A A	28	9.5	9.0 - 11.0	50	1929	26.7	10.9	10	1N+2S+2P
225/40ZR19	XL	93Y	500 A A	23	8.0	7.5 - 9.0	50	1433	26.1	9.1	9	1N+2S+1P
235/35ZR19	XL	91Y	500 A A	23	8.5	8.0 - 9.5	50	1356	25.5	9.5	9	1N+2S+1P
245/35ZR19	XL	93Y	500 A A	23	8.5	8.0 - 9.5	50	1433	25.8	9.8	9	1N+2S+1P
245/40ZR19	XL	98Y	500 A A	26	8.5	8.0 - 9.5	50	1653	26.7	9.8	9	1N+2S+2P
245/45ZR19	XL	102Y	500 A A	27	8.0	7.5 - 9.0	50	1874	27.7	9.6	9	1N+2S+2P
255/35ZR19	XL	96Y	500 A A	25	9.0	8.5 - 10.0	50	1565	26.0	10.2	9	1N+2S+2P
255/40ZR19	XL	100Y	500 A A	26	9.0	8.5 - 10.0	50	1764	27.0	10.2	9	1N+2S+2P
265/30ZR19	XL	93Y	500 A A	24	9.5	9.0 - 10.0	50	1435	25.3	10.7	9	1N+2S+1P
275/35ZR19	XL	100Y	500 A A	29	9.5	9.0 - 11.0	50	1764	26.6	10.9	9	1N+2S+2P
275/40ZR19	XL	105Y	500 A A	29	9.5	9.0 - 11.0	50	2039	27.7	10.9	9	1N+2S+2P
285/35ZR19	XL	103Y	500 A A	31	10.0	9.5 - 11.0	50	1929	26.9	11.4	9	1N+2S+2P
305/30ZR19	XL	102Y	500 A A	29	11.0	10.0 - 11.0	50	1875	26.3	12.3	9	1N+2S+2P
245/35ZR20	XL	95Y	500 A A	25	8.5	8.0 - 9.5	50	1521	26.8	9.8	9	1N+2S+1P
245/40ZR20	XL	99Y	500 A A	27	8.5	8.0 - 9.5	50	1709	27.7	9.8	9	1N+2S+2P
245/45ZR20	XL	103Y	500 A A	28	8.0	7.5 - 9.0	50	1929	28.7	9.6	9	1N+2S+2P
255/35ZR20	XL	97Y	500 A A	26	9.0	8.5 - 10.0	50	1609	27.0	10.2	9	1N+2S+2P
255/45ZR20	XL	105Y	500 A A	29	8.5	8.0 - 9.5	50	2039	29.1	10.0	9	1N+2S+2P
285/30ZR20	XL	99Y	500 A A	29	10.0	9.5 - 10.5	50	1709	26.8	11.4	9	1N+2S+2P
235/30ZR22	XL	90W	500 A A	25	8.5	8.0 - 9.0	50	1325	27.6	9.5	9	1N+2S+1P
245/30ZR22	XL	92W	500 A A	27	8.5	8.0 - 9.0	50	1389	27.8	9.8	9	1N+2S+2P
255/30ZR22	XL	95W	500 A A	28	9.0	8.5 - 9.5	50	1520	28.1	10.2	9	1N+2S+1P
275/30ZR24	XL	101Y	500 A A	32	9.5	9.0 - 10.0	50	1820	30.6	10.9	9	1N+2S+2P

* 25,000 Mile / 40,000 KM warranty for staggered fitments

All specifications subject to change

HIGHWAY-TERRAIN

Tormenta H/T

A dependable, all-season, light truck highway tire that delivers a smooth ride and extended mileage.



KEY ATTRIBUTES

60K
Metric

45K
LT

600
AB

M+S

POPULAR FITMENTS

- Toyota RAV4
- Ford Expedition
- Chevrolet Suburban
- Kia Sorento
- Nissan Rogue

FEATURES & BENEFITS

1. All-Season Optimized

Multiple siping shortens braking distances and improves overall safety and performance

2. Increased Wet Traction

Four wide grooves boost grip and handling when wet

3. Road Noise Resistant

Pattern Noise Simulation (PNS) produces a quieter ride

4. Material & Temperature Uniformity

Dual steel belt with nylon spiral wrap cap ply for uniformity and heat protection

5. Increased Durability

Nano Blend Compound ensures consistent performance over the lifecycle of the tire



**FORTUNE
TIRES** 

EXPECT MORE™

The most popular tire for light trucks, CUVs, and SUVs.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com





TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
215/75R15	SL	100T	600 A B	27	6.0	5.5 - 7.0	44	1764	27.7	8.5	12	1N+2S+2P
225/70R15	SL	100T	600 A B	28	6.5	6.0 - 7.5	44	1764	27.4	9.0	12	1N+2S+2P
225/75R15	SL	102T	600 A B	29	6.0	6.0 - 7.5	44	1874	28.3	8.8	12	1N+2S+2P
235/75R15	XL	109T	600 A B	31	6.5	6.0 - 8.0	50	2271	28.9	9.3	12	1N+2S+2P
215/70R16	SL	100H	600 A B	27	6.5	5.5 - 7.0	44	1764	27.9	8.7	12	1N+2S+2P
225/75R16	SL	104T	600 A B	30	6.0	6.0 - 7.5	44	1984	29.3	8.8	12	1N+2S+2P
235/70R16	SL	106T	600 A B	31	7.0	6.0 - 8.0	44	2094	29.0	9.4	12	1N+2S+2P
235/75R16	XL	112T	600 A B	32	6.5	6.0 - 8.0	50	2469	29.8	9.3	12	1N+2S+2P
245/70R16	SL	107T	600 A B	33	7.0	6.5 - 8.0	44	2149	29.5	9.8	12	1N+2S+2P
245/75R16	SL	111T	600 A B	35	7.0	6.5 - 8.0	44	2403	30.5	9.8	12	1N+2S+2P
255/70R16	SL	111T	600 A B	35	7.5	6.5 - 8.5	44	2403	30.1	10.2	12	1N+2S+2P
265/70R16	SL	112T	600 A B	37	8.0	7.0 - 9.0	44	2469	30.6	10.7	12	1N+2S+2P
265/75R16	SL	116T	600 A B	39	7.5	7.0 - 9.0	44	2756	31.7	10.5	12	1N+2S+2P
225/65R17	SL	102H	600 A B	27	6.5	6.0 - 8.0	44	1874	28.5	9.0	11	1N+2S+2P
235/65R17	XL	108H	600 A B	30	7.0	6.5 - 8.5	50	2205	29.1	9.4	11	1N+2S+2P
245/65R17	SL	107T	600 A B	31	7.0	7.0 - 8.5	44	2149	29.5	9.8	11	1N+2S+2P
245/70R17	SL	110T	600 A B	36	7.0	6.5 - 8.0	44	2337	30.6	9.8	12	1N+2S+2P
255/70R17	SL	112T	600 A B	36	7.5	6.5 - 8.5	44	2470	31.1	10.2	12	1N+2S+2P
265/65R17	SL	112T	600 A B	38	8.0	7.5 - 9.5	44	2469	30.6	10.7	12	1N+2S+2P
265/70R17	SL	115T	600 A B	39	8.0	7.0 - 9.0	44	2679	31.7	10.7	12	1N+2S+2P
235/60R18	XL	107V	600 A B	31	7.0	6.5 - 8.5	50	2149	29.1	9.4	11	1N+2S+2P
235/65R18	SL	106H	600 A B	31	7.0	6.5 - 8.5	44	2094	30.0	9.4	11	1N+2S+2P
245/60R18	SL	105H	600 A B	31	7.0	7.0 - 8.5	44	2039	29.6	9.8	11	1N+2S+2P
255/55R18	XL	109V	600 A B	32	8.0	7.0 - 9.0	50	2270	29.0	10.4	12	1N+2S+2P
255/65R18	SL	111H	600 A B	37	7.5	7.0 - 9.0	44	2403	31.1	10.2	12	1N+2S+2P
255/70R18	SL	113T	600 A B	39	7.5	6.5 - 8.5	44	2535	32.1	10.2	12	1N+2S+2P
265/60R18	SL	110H	600 A B	36	8.0	7.5 - 9.5	44	2337	30.5	10.7	11	1N+2S+2P
265/65R18	SL	114H	600 A B	39	8.0	7.5 - 9.5	44	2601	31.5	10.7	12	1N+2S+2P
265/70R18	SL	116T	600 A B	40	8.0	7.0 - 9.0	44	2756	32.6	10.7	12	1N+2S+2P
275/65R18	SL	116T	600 A B	41	8.0	7.5 - 9.5	44	2756	32.1	11.0	12	1N+2S+2P
225/55R19	SL	99V	600 A B	27	7.0	6.0 - 8.0	44	1710	28.8	9.2	11	1N+2S+2P
235/55R19	SL	101V	600 A B	29	7.5	6.5 - 8.5	44	1820	29.2	9.6	11	1N+2S+2P
245/55R19	SL	103V	600 A B	30	7.5	7.0 - 8.5	44	1930	29.6	10.0	11	1N+2S+2P
255/60R19	SL	109H	600 A B	37	7.5	7.0 - 9.0	44	2271	31.1	10.2	12	1N+2S+2P
235/55R20	SL	102V	600 A B	30	7.5	6.5 - 8.5	51	1875	30.2	9.6	11	1N+2S+2P
245/50R20	SL	102V	600 A B	30	7.5	7.0 - 8.5	44	1875	29.7	10.0	11	1N+2S+2P
255/55R20	XL	110H	600 A B	35	8.0	7.0 - 9.5	50	2335	31.0	10.4	12	1N+2S+2P
265/50R20	XL	111T	600 A B	36	8.5	7.5 - 9.5	50	2403	30.5	10.9	12	1N+2S+2P
275/55R20	SL	113H	600 A B	42	8.5	7.5 - 9.5	44	2535	31.9	11.2	12	1N+2S+2P
275/60R20	SL	115H	600 A B	42	8.0	7.5 - 9.5	44	2679	33.0	11.0	12	1N+2S+2P
275/50R22	XL	115H	600 A B	41	8.5	7.5 - 9.5	50	2680	32.9	11.1	12	1N+2S+2P
285/45R22	XL	114H	600 A B	39	9.5	9.0 - 10.5	50	2601	32.1	11.2	11	1N+2S+2P
LT235/75R15	6PR	104/101S	C	34	6.5	6.0 - 8.0	50	1985/1820	28.9	9.3	13	1N+2S+2P
LT215/85R16	10PR	115/112R	E	36	6.0	5.5 - 7.0	80	2680/2470	30.4	8.5	13	1N+2S+2P
LT225/75R16	10PR	115/112S	E	35	6.0	6.0 - 7.5	80	2680/2470	29.3	8.8	13	1N+2S+2P
LT235/85R16	10PR	120/116S	E	40	6.5	6.0 - 7.5	80	3042/2778	31.7	9.3	13	1N+2S+2P
LT245/75R16	10PR	120/116S	E	39	7.0	6.5 - 8.0	80	3042/2778	30.5	9.8	13	1N+2S+2P
LT265/75R16	10PR	123/120S	E	45	7.5	7.0 - 9.0	80	3415/3085	31.7	10.5	14	1N+2S+2P
LT235/80R17	10PR	120/117R	E	41	6.5	6.0 - 8.0	80	3085/2835	31.8	9.3	13	1N+2S+2P
LT245/75R17	10PR	121/118S	E	41	7.0	6.5 - 8.0	80	3195/2910	31.5	9.8	13	1N+2S+2P
LT265/70R17	10PR	123/120S	E	44	8.0	7.0 - 9.0	80	3415/3085	31.7	10.7	14	1N+2S+2P
LT265/70R18	10PR	124/121S	E	48	8.0	7.0 - 9.0	80	3525/3195	32.6	10.7	14	1N+2S+2P
LT275/65R18	10PR	123/120S	E	51	8.0	8.0 - 9.5	80	3415/3085	32.1	11.0	14	1N+2S+2P
LT275/70R18	10PR	125/122S	E	51	8.0	7.0 - 9.0	80	3640/3305	33.2	11.0	14	1N+2S+2P
LT275/65R20	10PR	126/123S	E	53	8.0	8.0 - 9.5	80	3750/3415	34.1	11.0	14	1N+2S+2P
LT285/50R20	10PR	119/116S	E	47	9.0	8.5 - 10.0	80	3000/2755	31.3	11.7	13	1N+2S+2P

All specifications subject to change

ALL-TERRAIN ALL-WEATHER

Tormenta A/T²

A superior all-terrain, all-weather, light truck and SUV tire with an aggressive look and upgraded sidewall.



KEY ATTRIBUTES



POPULAR FITMENTS

- Ford F150
- Ram 1500
- Toyota Tacoma
- Chevy Silverado
- Jeep Gladiator

ALL-WEATHER RATED



RAIN



MIX



SNOW



HEAT

FEATURES & BENEFITS

1. Aggressive Tread Design

Optimized for better traction and stability on any terrain, prioritizing control and safety

2. Road Noise Resistant

Pattern Noise Simulation (PNS) produces a quieter ride

3. OWL Sidewall

Select sizes come with outline white letter styling on one sidewall

4. Upgraded Sidewall

Reinforced sidewall protects against punctures in rugged environments

5. All-Weather Optimized

3PMS-rated for superior performance in wet and wintry conditions



**FORTUNE
TIRES**

EXPECT MORE™

42 SKUs capable of handling any terrain.

Contact a sales representative at fortunetireusa.com/dealer-contact



Scan to see our full lineup

fortunetireusa.com





TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
235/75R15*	XL	109T	600 A A	36	6.5	6.0 - 8.0	50	2271	28.9	9.3	13	1N+2S+2P
245/75R16*	SL	111T	600 A A	40	7.0	6.5 - 8.0	51	2403	30.5	9.8	13	1N+2S+2P
265/75R16*	SL	116T	600 A A	44	7.5	7.0 - 9.0	51	2756	31.7	10.5	13	1N+2S+2P
225/65R17*	XL	106T	600 A A	37	6.5	6.0 - 8.0	50	2094	28.5	9.0	13	1N+2S+2P
245/65R17*	XL	111T	600 A A	36	7.0	7.0 - 8.5	50	2403	29.5	9.8	13	1N+2S+2P
245/70R17*	SL	110T	600 A A	40	7.0	6.5 - 8.0	51	2337	30.6	9.8	13	1N+2S+2P
245/75R17*	SL	112T	600 A A	42	7.0	6.5 - 8.0	51	2469	31.5	9.8	13	1N+2S+2P
265/65R17*	SL	112T	600 A A	41	8.0	7.5 - 9.5	51	2469	30.6	10.7	13	1N+2S+2P
265/70R17*	SL	115T	600 A A	40	8.0	7.0 - 9.0	51	2679	31.7	10.7	13	1N+2S+2P
255/70R18*	SL	113T	600 A A	44	7.5	7.0 - 9.0	51	2535	32.1	10.2	13	1N+2S+2P
265/65R18*	SL	114T	600 A A	44	8.0	7.5 - 9.5	51	2601	31.5	10.7	13	1N+2S+2P
275/65R18*	SL	116H	600 A A	46	8.0	7.5 - 9.5	51	2756	32.1	11.0	13	1N+2S+2P
275/55R20	XL	117T	600 A A	41	8.5	7.5 - 9.5	50	2833	31.9	11.2	13	1N+2S+2P
275/60R20	XL	116T	600 A A	47	8.0	7.5 - 9.5	50	2756	33.0	11.0	13	1N+2S+2P
LT225/75R16*	10PR	115/112S	E	38	6.0	6.0 - 7.5	80	2680/2470	29.3	8.8	16	1N+2S+2P
LT235/85R16*	10PR	120/116R	E	42	6.5	6.0 - 7.5	80	3042/2778	31.7	9.3	16	1N+2S+2P
LT245/75R16*	10PR	120/116S	E	42	7.0	6.5 - 8.0	80	3042/2778	30.5	9.8	16	1N+2S+2P
LT265/75R16*	10PR	123/120S	E	47	7.5	7.0 - 9.0	80	3415/3085	31.7	10.5	16	1N+2S+2P
LT285/75R16*	10PR	126/123R	E	43	8.0	7.5 - 9.5	80	3740/3415	32.8	11.3	16	1N+2S+2P
LT235/80R17*	10PR	120/117R	E	44	6.5	6.0 - 8.0	80	3085/2835	31.8	9.3	16	1N+2S+2P
LT245/70R17*	10PR	121/118S	E	45	7.0	6.5 - 8.0	80	3195/2910	31.5	9.8	16	1N+2S+2P
LT265/70R17*	10PR	123/120S	E	48	8.0	7.0 - 9.0	80	3415/3085	31.7	10.7	16	1N+2S+2P
LT285/70R17*	10PR	126/123S	E	42	8.5	7.5 - 9.5	80	3750/3415	32.8	11.5	16	1N+2S+2P
LT315/70R17*	10PR	126/123S	E	61	9.5	8.0 - 10.5	65	3750/3415	34.4	12.7	16	1N+2S+2P
LT265/70R18*	10PR	124/121S	E	49	8.0	7.0 - 9.0	80	3525/3195	32.6	10.7	16	1N+2S+2P
LT275/65R18*	10PR	123/120S	E	53	8.0	8.0 - 9.5	80	3415/3085	32.1	11.0	16	1N+2S+2P
LT275/70R18*	10PR	125/122S	E	53	8.0	7.0 - 9.0	80	3640/3305	33.2	11.0	16	1N+2S+2P
LT325/65R18*	10PR	127/124R	E	63	9.5	9.5 - 11.5	65	3860/3525	34.6	13.0	16	1N+2S+2P
LT265/60R20	10PR	121/118S	E	39	8.0	8.0 - 9.5	80	3195/2910	32.5	10.7	16	1N+2S+2P
LT275/65R20*	10PR	126/123S	E	57	8.0	8.0 - 9.5	80	3750/3415	34.1	11.0	16	1N+2S+2P
LT285/55R20	10PR	122/119S	E	53	9.0	8.5 - 10.0	80	3305/3000	32.4	11.7	16	1N+2S+2P
LT285/60R20	10PR	125/122Q	E	55	8.5	8.5 - 10.0	80	3640/3305	33.5	11.5	16	1N+2S+2P
LT305/55R20	12PR	125/122Q	F	64	9.5	9.0 - 11.0	80	3640/3305	33.2	12.4	16	2N+2S+3P
LT325/60R20	10PR	126/123S	E	67	9.5	9.5 - 11.5	80	3750/3415	35.4	13.0	16	1N+2S+2P
31X10.50R15LT*	6PR	109S	C	47	8.5	7.0 - 9.0	50	2270	30.5	10.6	16	1N+2S+2P
35X12.50R17LT*	12PR	128S	F	62	10.0	8.0 - 10.5	80	3970	34.5	12.5	16	2N+2S+3P
35X12.50R18LT*	12PR	128S	F	59	10.0	8.5 - 11.0	80	3970	34.5	12.5	16	2N+2S+3P
33X12.50R20LT	12PR	119S	F	63	10.0	8.5 - 11.0	80	3000	32.5	12.5	16	2N+2S+3P
35X12.50R20LT	12PR	125S	F	64	10.0	8.5 - 11.0	80	3640	34.5	12.5	16	2N+2S+3P
35X12.50R22LT	12PR	121S	F	68	10.0	8.5 - 11.0	80	3195	34.5	12.5	16	2N+2S+3P
37X12.50R22LT	12PR	127S	F	75	10.0	8.5 - 11.0	80	3860	36.5	12.5	16	2N+2S+3P

*OWL sidewall

All specifications subject to change

RUGGED-TERRAIN

Tormenta R/T

A muscular, all-season, rugged terrain, light truck tire with good overall mileage performance.



KEY ATTRIBUTES

50K
LT

M+S

TSMI 15

POPULAR FITMENTS

- Ram 2500
- Jeep Gladiator
- Jeep Wrangler
- Ford Bronco
- Chevy Silverado

FEATURES & BENEFITS

1. Increased Stability

Aggressive tread design with multi-step blocks for added stability and durability

2. Debris Clearing Capability

Mud movers and rippers in center tread blocks clear debris for better traction

3. Snow Stud Ready

Studdable using TSMI #15

4. Reinforced Sidewall

Rugged 3-ply sidewall offers additional protection in off-road environments

5. Alternate Sidewall Styles

The two sides of the tire feature different sidewall designs, offering the driver a choice



**FORTUNE
TIRES** 

EXPECT MORE™

Easily handle the most demanding conditions.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com





TIRE SIZE	LOAD PR	LT/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
LT265/65R17	10PR	120/117Q	E	51	8.0	8.0 - 9.5	80	3085/2835	30.6	10.7	17	1N+2S+3P
LT265/70R17	10PR	123/120Q	E	54	8.0	7.0 - 9.0	80	3415/3085	31.7	10.7	17	1N+2S+3P
LT285/70R17	10PR	126/123Q	E	57	8.5	7.5 - 9.5	80	3750/3415	32.8	11.5	17	1N+2S+3P
LT295/70R17	10PR	128/125Q	E	60	8.5	7.5 - 10.0	80	3970/3640	33.3	11.8	17	1N+2S+3P
LT265/60R18	10PR	119/116Q	E	51	8.0	8.0 - 9.5	80	3000/2755	30.5	10.7	17	1N+2S+3P
LT265/65R18	10PR	122/119Q	E	54	8.0	8.0 - 9.5	80	3305/3000	31.5	10.7	17	1N+2S+3P
LT265/70R18	10PR	124/121Q	E	56	8.0	7.0 - 9.0	80	3525/3195	32.6	10.7	17	1N+2S+3P
LT275/65R18	10PR	123/120Q	E	57	8.0	8.0 - 9.5	80	3425/3085	32.1	11.0	17	1N+2S+3P
LT275/70R18	10PR	125/122Q	E	59	8.0	7.0 - 9.0	80	3640/3305	33.2	11.0	17	1N+2S+3P
LT285/60R18	10PR	122/119Q	E	56	8.5	8.5 - 10.0	80	3305/3000	31.5	11.5	17	1N+2S+3P
LT285/65R18	10PR	125/122Q	E	59	8.5	8.5 - 10.0	80	3640/3305	32.6	11.5	17	1N+2S+3P
LT285/75R18	10PR	129/126Q	E	64	8.0	7.5 - 9.5	80	4080/3750	34.8	11.3	17	1N+2S+3P
LT295/70R18	10PR	129/126Q	E	64	8.5	7.5 - 10.0	80	4080/3750	34.3	11.8	17	1N+2S+3P
LT265/50R20	10PR	115/112Q	E	53	8.5	8.0 - 9.5	80	2680/2470	30.5	10.9	17	1N+2S+3P
LT275/55R20	10PR	120/117Q	E	58	8.5	8.5 - 10.0	80	3085/2835	31.9	11.2	17	1N+2S+3P
LT275/60R20	10PR	123/120Q	E	58	8.0	8.0 - 9.5	80	3415/3085	33.0	11.0	17	1N+2S+3P
LT275/65R20	10PR	126/123Q	E	61	8.0	8.0 - 9.5	80	3750/3415	34.1	11.0	17	1N+2S+3P
LT285/50R20	10PR	119/116Q	E	57	9.0	8.5 - 10.0	80	3000/2755	31.3	11.7	17	1N+2S+3P
LT285/55R20	10PR	122/119Q	E	59	9.0	8.5 - 10.0	80	3305/3000	32.4	11.7	17	1N+2S+3P
LT285/60R20	10PR	125/122Q	E	61	8.5	8.5 - 10.0	80	3640/3305	33.5	11.5	17	1N+2S+3P
LT295/55R20	10PR	123/120Q	E	62	9.5	8.5 - 10.5	80	3415/3085	32.8	12.2	17	1N+2S+3P
LT295/60R20	10PR	126/123Q	E	63	8.5	8.5 - 10.5	80	3750/3415	33.9	11.8	17	1N+2S+3P
LT295/65R20	10PR	129/126Q	E	67	8.5	8.5 - 10.5	80	4080/3750	35.1	11.8	17	1N+2S+3P
LT305/55R20	10PR	121/118Q	E	66	9.5	9.0 - 11.0	65	3195/2910	34.1	12.4	18	1N+2S+3P
LT325/60R20	10PR	126/123Q	E	72	9.5	9.5 - 11.5	65	3750/3415	35.4	13.0	18	1N+2S+3P
LT285/50R22	10PR	121/118Q	E	60	9.0	8.5 - 10.0	80	3195/2910	33.3	11.7	17	1N+2S+3P
LT325/50R22	12PR	127Q	F	73	10.0	9.5 - 11.5	80	3860	34.8	13.2	18	1N+2S+3P
35X12.50R17LT	12PR	128Q	F	68	10.0	8.0-10.5	80	3970	34.5	12.5	18	1N+2S+3P
35X12.50R17LT	10PR	128Q	E	71	10.0	8.0 - 10.5	65	3970	36.5	12.5	18	1N+2S+3P
37X13.50R17LT	10PR	128Q	E	77	11.0	9.0 - 11.5	65	3970	36.5	13.6	18	1N+2S+3P
33X12.50R18LT	12PR	122Q	F	64	10.0	8.5 - 11.0	80	3305	32.5	12.5	18	1N+2S+3P
35X12.50R18LT	12PR	128Q	F	68	10.0	8.5 - 11.0	80	3970	34.5	12.5	18	1N+2S+3P
37X13.50R18LT	12PR	128Q	F	78	11.0	9.5 - 12.0	80	3970	36.5	13.6	18	1N+2S+3P
33X12.50R20LT	12PR	119Q	F	65	10.0	8.5 - 11.0	80	3000	32.5	12.5	18	1N+2S+3P
35X12.50R20LT	10PR	121Q	F	69	10.0	8.5 - 11.0	65	3195	34.5	12.5	18	1N+2S+3P
35X12.50R20LT	12PR	125Q	F	69	10.0	8.5 - 11.0	80	3640	34.5	12.5	18	1N+2S+3P
35X13.50R20LT	10PR	121Q	E	73	11.0	9.5 - 12.0	65	3195	34.5	13.6	18	1N+2S+3P
37X12.50R20LT	10PR	126Q	E	73	10.0	8.5 - 11.0	65	3750	36.5	12.5	18	1N+2S+3P
37X13.50R20LT	10PR	127Q	E	79	11.0	9.5 - 12.0	65	3860	36.5	13.6	18	1N+2S+3P
33X12.50R22LT	12PR	114Q	F	66	10.0	8.5 - 11.0	80	2600	32.5	12.5	18	1N+2S+3P
35X12.50R22LT	10PR	117Q	E	69	10.0	8.5 - 11.0	65	2835	34.5	12.5	18	1N+2S+3P
37X12.50R22LT	10PR	123Q	E	73	10.0	8.5 - 11.0	65	3415	36.5	12.5	18	1N+2S+3P
37X13.50R22LT	10PR	123Q	E	79	11.0	9.5 - 12.0	65	3415	36.5	13.6	18	1N+2S+3P
35X12.50R24LT	12PR	116Q	F	69	10.5	10.0 - 12.0	80	2755	34.5	12.5	18	1N+2S+3P
37X13.50R24LT	12PR	124Q	F	80	11.0	9.5 - 12.0	80	3525	36.5	13.6	18	1N+2S+3P
40X15.50R24LT	10PR	128Q	F	97	12.5	11.0 - 14.0	65	3970	39.5	15.6	18	1N+2S+3P

All specifications subject to change

MUD-TERRAIN

Tormenta M/T

An all-season light truck tire geared for the most extreme terrain and off-road conditions.



KEY ATTRIBUTES



POPULAR FITMENTS

- Ram 2500
- Jeep Gladiator
- Jeep Wrangler
- Ford Bronco
- Ford F150

FEATURES & BENEFITS

1. Increased Stability

Wide pattern block design improves stability and wear resistance in harsh conditions

2. Debris Clearing Capability

Mud movers and rippers in center tread blocks clear debris for better traction

3. Snow Stud Ready

Studdable using TSMI #15

4. Reinforced Sidewall

Rugged 3-ply sidewall offers additional protection in off-road environments



**FORTUNE
TIRES** 

EXPECT MORE™

Aggressive lugs and 3-ply reinforced sidewall.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com



Tormenta M/T

TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
LT235/75R15	8PR	110/107Q	D	40	6.5	6.0 - 8.0	65	2335/2150	28.9	9.3	18	1N+2S+2P
LT235/85R16	10PR	120/116Q	E	48	6.5	6.0 - 7.5	80	3042/2778	31.7	9.3	18	1N+2S+3P
LT245/75R16	10PR	120/116Q	E	48	7.0	6.5 - 8.0	80	3042/2778	30.5	9.8	18	1N+2S+3P
LT265/75R16	10PR	123/120Q	E	55	7.5	7.0 - 9.0	80	3415/3085	31.7	10.5	19	1N+2S+3P
LT285/75R16	10PR	126/123Q	E	60	8.0	7.5 - 9.5	80	3750/3415	32.8	11.3	20	1N+2S+3P
LT305/70R16	10PR	124/121Q	E	62	9.0	8.0 - 10.0	65	3525/3195	32.8	12.2	20	1N+2S+3P
LT265/70S17	10PR	123/120Q	E	54	8.0	7.0 - 9.0	80	3415/3085	31.7	10.7	19	1N+2S+3P
LT285/70R17	10PR	126/123Q	E	61	8.5	7.5 - 9.5	80	3750/3415	32.8	11.5	20	1N+2S+3P
LT275/65R18	10PR	123/120Q	E	58	8.0	8.0 - 9.5	80	3415/3085	32.1	11.0	19	1N+2S+3P
LT305/55R20	10PR	121/118Q	E	66	9.5	9.0 - 11.0	65	3195/2910	33.2	12.4	20	1N+2S+3P
LT325/50R22	10PR	122Q	E	74	10.0	9.5 - 11.5	65	3305	34.8	13.2	20	1N+2S+3P
31X10.50R15LT	6PR	109Q	C	48	8.5	7.0 - 9.0	50	2270	30.5	10.6	20	1N+2S+2P
33X12.50R15LT	6PR	108Q	C	62	10.0	8.0 - 10.5	35	2205	32.5	12.5	20	1N+2S+3P
35X12.50R17LT	12PR	128Q	F	67	10.0	8.0 - 10.5	80	3970	34.5	12.5	20	1N+2S+3P
33X12.50R18LT	10PR	118Q	E	66	10.0	8.5 - 11.0	65	2910	32.5	12.5	20	1N+2S+3P
35X12.50R18LT	10PR	123Q	E	69	10.0	8.5 - 11.0	65	3415	34.5	12.5	20	1N+2S+3P
33X12.50R20LT	10PR	114Q	E	66	10.0	8.5 - 11.0	65	2600	32.5	12.5	20	1N+2S+3P
33X12.50R20LT	12PR	119Q	F	66	10.0	8.5 - 11.0	80	3000	36.5	12.5	20	1N+2S+3P
35X12.50R20LT	10PR	121Q	E	71	10.0	8.5 - 11.0	65	3195	34.5	12.5	20	1N+2S+3P
25X12.50R20LT	12PR	125Q	F	71	10.0	8.5 - 11.0	80	3640	34.5	12.5	20	1N+2S+3P
37X12.50R20LT	12PR	128Q	F	75	10.0	8.5 - 11.0	80	3970	36.5	12.5	20	1N+2S+3P
37X13.50R20LT	10PR	127Q	E	81	11.0	9.5 - 12.0	65	3860	36.5	13.6	21	1N+2S+3P
37X13.50R20LT	12PR	128Q	F	82	11.0	9.5 - 12.0	80	3970	36.5	13.6	21	1N+2S+3P
33X12.50R22LT	10PR	109Q	E	65	10.0	8.5 - 11.0	65	2270	32.5	12.5	19	1N+2S+3P
35X12.50R22LT	12PR	121Q	F	71	10.0	8.5 - 11.0	80	3195	34.5	12.5	20	1N+2S+3P
37X12.50R22LT	12PR	127Q	F	76	10.0	8.5 - 11.0	80	3860	36.5	12.5	20	1N+2S+3P
37X13.50R22LT	12PR	128Q	F	82	11.0	9.5 - 12.0	80	3970	36.5	13.6	21	1N+2S+3P

All specifications subject to change

COMMERCIAL FLEET

Tormenta LMD

An all-weather rated, last mile delivery vehicle tire, engineered for vans and commercial light trucks.



KEY ATTRIBUTES



POPULAR FITMENTS

- Ford Transit
- Nissan NV200
- Chevy City Express
- Mercedes Sprinter 3500
- Ford F150

ALL-WEATHER RATED



RAIN



MIX



SNOW



HEAT

FEATURES & BENEFITS

1. Increased Wet Traction

Four wide grooves effectively evacuate water for better grip

2. Enhanced Wet Braking

High-depth sipes with increased biting edges resist hydroplaning

3. Improved Wear Pattern

Tie-bar linked tread blocks prevent irregular wear

4. Puncture Resistant

A thicker under-tread and reinforced belt prevent damage from road debris

5. All-Weather Optimized

3PMS-rated for superior performance in wet and wintry conditions

6. Reinforced Sidewall

Strengthened sidewalls utilize a special compound that resists curb and high-scrub damage while increasing load capacity.



**FORTUNE
TIRES** 

EXPECT MORE™

3PMS-rated for performance
in rain, heat, or snow.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup


fortunetireusa.com



Tormenta LMD

TIRE SIZE	LOAD PR	LI/SR (SINGLE/DUAL)	UTQG LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
185/60R15C	6PR	94/92T	C	22	5.5	5.0 - 6.0	54	1477/1389	23.7	7.4	13	1N+2S+2P
195/75R16C	8PR	107/105R	D	28	5.5	5.0 - 6.0	69	2150/2040	27.5	7.7	13	1N+2S+2P
205/75R16C	10PR	113/111R	E	31	5.5	5.0 - 6.0	76	2535/2405	28.1	8.0	13	1N+2S+2P
225/75R16C	10PR	121/120R	E	36	6.0	6.0 - 7.0	83	3195/3085	29.3	8.8	13	1N+2S+2P
235/65R16C	10PR	121/119R	E	35	7.0	6.5 - 7.5	80	3195/3000	28.0	9.4	13	1N+2S+2P
LT215/85R16	10PR	115/112R	E	35	6.0	5.5 - 7.0	80	2680/2470	30.4	8.5	13	1N+2S+2P
LT225/75R16	10PR	115/112R	E	35	6.0	6.0 - 7.5	80	2680/2470	29.3	29.3	13	1N+2S+2P
LT235/85R16	10PR	120/116R	E	38	6.5	6.0 - 7.5	80	3042/2778	31.7	9.3	13	1N+2S+2P
LT245/75R16	10PR	120/116S	E	41	7.0	6.5 - 8.0	80	3042/2778	30.5	9.8	13	1N+2S+2P
LT265/75R16	10PR	123/120R	E	43	7.5	7.0 - 9.0	80	3415/3085	31.7	10.5	14	1N+2S+2P
LT235/80R17	10PR	120/117R	E	38	6.5	6.0 - 8.0	80	2085/2835	31.8	9.3	13	1N+2S+2P
LT245/70R17	10PR	119/116S	E	38	7.0	6.5 - 8.0	80	3000/2755	30.6	9.8	13	1N+2S+2P
LT245/75R17	10PR	121/118S	E	40	7.0	6.5 - 8.0	80	3195/2910	31.5	9.8	13	1N+2S+2P
LT265/70R17	10PR	123/120R	E	44	8.0	7.0 - 9.0	80	3415/3085	31.7	10.5	14	1N+2S+2P
LT275/65R18	10PR	123/120R	E	48	8.0	8.0 - 9.5	80	3415/3085	32.1	11.0	14	1N+2S+2P
LT275/70R18	10PR	125/122S	E	50	8.0	7.0 - 9.0	80	3640/3305	33.2	11.0	14	1N+2S+2P

All specifications subject to change



SPECIALTY TRAILER

ST01

A dependable, all-purpose trailer tire with a reinforced sidewall for improved load capacity.



KEY ATTRIBUTES



- For trailer use only

POPULAR FITMENTS

- Boat Trailers
- Horse Trailers
- Campers
- Toy Haulers
- Landscape Trailers

FEATURES & BENEFITS

1. Increased Stability

Continuous center rib for better stability and tracking

2. Material & Temperature Uniformity

Nylon spiral wrap for improved uniformity and protection against heat buildup

3. Reinforced Sidewall

Strengthened sidewall construction for improved load capability against curb damage



**FORTUNE
TIRES** 

EXPECT MORE™

Reinforced construction
for heavy loads.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup


fortunetireusa.com



ST01

TIRE SIZE	PR	LI/SR (SINGLE/ DUAL)	LOAD RANGE	WEIGHT (LBS)	MEASURING RIM WIDTH (IN)	APPROVED RIM WIDTH (MIN-MAX)	MAX PRESSURE (PSI)	MAX LOAD (SINGLE/ DUAL)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32ND)	TREAD CONSTRUCTION
ST175/80R13	8PR	97/93L	D	17	5.0	4.5 - 6.0	65	1609/1433	24.0	7.0	8	1N+2S+2P
ST205/75R14	8PR	105/101M	D	22	5.5	5.0 - 7.0	65	2040/1820	26.1	8.0	8	1N+2S+2P
ST215/75R14	8PR	108/103L	D	24	6.0	5.5 - 7.0	65	2205/1929	26.7	8.5	8	1N+2S+2P
ST205/75R15	6PR	101/97M	C	21	5.5	5.0 - 7.0	50	1820/1610	27.1	8.0	8	1N+2S+2P
ST205/75R15	8PR	107/102M	D	22	5.5	5.0 - 7.0	65	2150/1870	27.1	8.0	8	1N+2S+2P
ST225/75R15	8PR	113/108M	D	26	6.0	6.0 - 7.5	65	2540/2200	28.3	8.8	8	1N+2S+2P
ST225/75R15	10PR	117/112M	E	27	6.0	6.0 - 7.5	80	2830/2470	28.3	8.8	8	1N+2S+2P
ST235/80R16	10PR	124/120M	E	31	6.5	6.0 - 7.5	80	3520/3080	30.8	9.3	8	1N+2S+2P
ST235/85R16	10PR	125/121M	E	34	6.5	6.0 - 7.5	80	3640/3200	31.7	9.3	8	1N+2S+2P

All specifications subject to change



HEAVY DUTY TRAILER

FST02

A heavy duty, all-steel trailer with increased load-bearing capacity and outstanding durability.



KEY ATTRIBUTES



- For trailer use only

FEATURES & BENEFITS

1. Enhanced Durability

New polybutadiene rubber and optimized footprint shape ensures excellent wear-resistance performance

2. Increased Traction

Unique sipe distribution offers good tire traction, handling, and safety

3. Stone Drilling Resistant

Tread groove geometry reduces stone retention



**FORTUNE
TIRES** 

EXPECT MORE™

Increased load-bearing capacity and durability.

Contact a sales representative at
fortunetireusa.com/dealer-contact



Scan to see our
full lineup

fortunetireusa.com



FST02

TIRE SIZE	PR/ LOAD RANGE	LOAD SPEED INDEX	TREAD DEPTH (32ND)	MAX LOAD SINGLE (LBS)	MAX PRESSURE SINGLE (PSI)	MAX LOAD DUAL (LBS)	MAX PRESSURE DUAL (PSI)	MEASURING RIM	APPROVED RIM WIDTH (IN)	O.D. (IN)	S.W. (IN)	REVS/ MILE	WEIGHT (LBS)	TREAD CONSTRUCTION
ST225/90R16	14G	129/125L	13	4080	110	3640	110	6.0	6.00 - 7.00	31.8	8.7	654	60	1S+3S
ST235/85R16	14G	132/127L	12	4400	110	3860	110	6.5	6.00 - 7.50	31.7	9.3	657	61	1S+3S
ST235/80R16	14G	129/125L	12	4080	110	3640	110	6.5	6.00 - 8.00	30.8	9.3	675	60	1S+3S

All specifications subject to change

